



des 14, 2025, & Olyen Union D. Hins D. Ubers (place) (stee Stacks Draybers) (des

WALL LEGEND:

EXTERIOR WALL - MASCHRY OVER 214 WOOD STUDS & 16° O.C. WITH I OFFSUM BOARD SISTE & I OFFSUM BOARD SISTEM SHEATHING OUTSIDE (OR SIMILAR).

DITTRICK WALL - 234 WOOD STUDS 4 IG*O, C. WITH # GIFSUM BOARD INDICE 4- DENS CLASS COLD SHEATHING OUTSIDE OR SIMILARI,

HITERIOR WALL - 2X4 WOOD STUDS 4 I C O.C. WITH \$ CHTSUM SCARD ON BOTH SIDES.

GENERAL NOTES:

- CENERAL CONTRACTOR SHALL VEREYFALL DIMENSIONS AND DESTING CONTRIONS AT THE UND SITE DEFORE COMMENCING ANY PLANE OF THE WORK, ADJUSTMENTD FOR IT AND COORDINATION SHALL DE MADE AT NO ADDITIONAL COST TO THE OWNER. NOTIFY DESIGNED OF ANY CONFLICTS. DISCREPANCES OR OMESSIONS FROM TO COMMENCIATION OF THE CONTRACT WORK.

Table R402.4.1.1

TABLE BIDZ 4 1.1

Air barder and thermal barder	A continuous six harder shall be installed in the building arrapione. Extends thermal available contains a continuous six berrier. Branks or joints in the air berrier shall be sopied. Alcoetmaskie josuistica shall not be used as a restling material.
Celling/etile	The sit harder in any drouped celling/politic that it and one destruits and ony despite the sit harder registed. Accurate counties, droug drown stait or intervent dates in unconditioned attice and a stail har registed.
YYnth .	The landion of the foundation and dilicials that he ageled. The landion of the for picks and loss of extends wells that he resied. Knee walls their be seeled.
Windows, skylights and dopra	The appen between windowateer tembrand framing and thrights and Paming shall be replay.
Rim feiste	Rimioble shall include the nichemier
Floors (including above-patrice and capitalist and floors)	The air harrier shall be installed at any excessed adon of insulation.
Shalls, penetrations	Duck shafts, willife constrained and flue shafts opening to exterior or unconditioned react shall be sayled.
Garage raparation	Recent benefithed bee southed between the estron and confidence spaces.
Received lighting	Receased fight fatures incisited in the building thermal enrators and be air light in rated and sasind to the stroyell.
Showsthub on exterior wall	Extense walls aging only to showers and jubs that have an or harrier installed appropriate them from the showers and jubs.
Electrice/ohone box on exterior wells	The air berrier than be installed behind six sides or communication by we or air sanied boxes that he installed.
HVAC register peots	HVAC (spirits boots that penetrate building thermal encappe shall be so eled to the subfloot or stress.
Eiteologo	An air barrin; mail ba installed on Grapiaca walls. Expolaces shall have tight giting digits.

a. In addition, importion of big wase shall be in accordance with the provisions of ICC-400.

Medify Section R402.2 and add new Section R402.2.1.

R402.2 Specific insulation requirements (Prescriptive). In addition to the requirements of Section R402.1, insulation shall meet the specific requirements of Sections R402.2.1 through R402.2.12. <u>Insulation shall aim his installed in accordance with Table R402.2</u>

TABLE 8402.2	
PUBLICATION DUST ALLATE	

PIRILATION PINTALLATION				
COMPONENT	CRIT BRIAN			
Karchy ionnistion installatión	All certifies in this in terminal armosing, shell, as little with insteadion. The dentative of the mention and the a thin savent dentative model a comment of the control o			
Colling/stitc	The sit hards in any dropped critical coll chell be siloned with the insulation. Ratinaulation installed in sits roof assemblies may be compressed at extends, well long to above for requiring antic varieties.			
Y/alis	Chiners and headate shall be inculpted. Edetics tharmal anything inculption for framed write shall be incitated in substantial contact and continuous alignment with the left harder.			
Rim biss	Rim joints what he josulated.			
Figure (including above garage and cardiavers (including above garage and cardiavers)				
Convigonce walls	Where crevised in linu of fleet insulation, insulation stalling nationality attended to the cramitizate sight. Excepted pattle in prevaints count one can shall be covered with a Class I vapor stated a with creategation birth staged.			
Namus curiles	Ratis in narrow cavillas shall be cut o fl. or narrow navillas shall be filled by intrinsicion intri en intellation resulty conformate the navilable nearlier parts. Paris in narrow configer shall be not to flaund intellated to the context gaveity witness and verifies or some or compression. Narrow cavillas shall be filled by intellection in intellation respire conformation in a reliable narrow pare.			
Plumbing and witing	But insulation shall be and neally to the around within and alumbing in exterior waits. There shall be not voice to support communities which got to fill insulation that a nit statistical readily conforms to weighble states shall extend behind a bits such which a bits such which is the said which of the said which is said which of the			

HO. DATE





EW RESIDENCE 1092 TX-46 NEW BRAUNFELS, TEXAS FLOOR PLAN

NEW

DRAWN ___RL CHECKED......DA

DATE_ A2.0